WINDOW TREATMENTS

FROSTED TRANSLUCENT FILMS

MATERIAL INFORMATION

3MTM

Description: 3M CRYSTAL Glass Finishes offer both dusted and frosted designs

that provide the look of sandblasted or etched glass, at a fraction of the cost. Can digitally print custom patterns, shapes and logos for a truly custom look. The product has a permanent, pressure sensitive adhesive and a transparent polyester liner for easy cutting. Available in dusted or frosted white crystal finish

and siz translucent colors.

Maximum width: 48" frosted (six translucent colors)

60" dusted white & frosted white

Thickness: Film + Adhesive 3.2 mil (81 microns) Dusted white

4.7 mil (120 microns) All frosted materials

Liner 3.6 mil (90 microns)

Physicals: Film is a superior quality printable vinyl

Pressure sensitive acrylic adhesive - Permanent

Silicone-coated polyester release liner May be cleaned 30 days after installation



Can be used for interior or exterior applications, including architectural window decorations, distraction graphics for privacy, custom interior branding and signage, separation panels and isolation graphics. Expected performance life is 15 years for vertical, indoor applications on non-perimeter glass.

GENERAL PROPERTIES

Application surface type: Flat

Application surface material: Glass, acrylic, polycarbonate

Application location: Interior and exterior

Application temp range: 54°F - 100°F (12°C - 38°C) air & application surface

Application method: Wet application

Product shrinkage: 0.01 in (0.3mm) maximum

Exposure temperature range: - 40°F - 149°F (- 40°C - 65°C)

Product removal: Low heat, or 3M Adhesive remover citrus

base and scraper

3M FROSTED

3M FROSTED
Printable Window Film



FIRE RESISTANCE

When used for interior applications, products have a Class A rating (as defined by NFPA 101 "Life Safety Code". Test method ASTM E84)

PRODUCT USE ADVISORY

Not recommended for interior applications where condensation consistently occurs