

WINDOW TREATMENTS

LONG-TERM ONE-WAY VISION WINDOW FILM

MATERIAL INFORMATION POLYMERIC VINYL

| | | |
|--------------|---|--|
| Description: | ASTM E84 Certified perforated pressure sensitive window film specially designed for long-term applications. Multiple options available for controlling the amount of open area vs printed area provides for wide range of applications. The product is made with polymeric vinyl with a clear semi-permanent adhesive and is ASTM E84 certified. | |
| Width: | 54" | |
| Thickness: | Film | 6 mil (145 micron) |
| | Adhesive | Self adhesive |
| | Liner | 4 mil universal paper liner or 1.7 mil clear liner |
| Physicals: | Polymetric vinyl with printable white front face Black reverse side provides for maximum contrast and image quality Excellent long term life span at normal conditions Self adhesive liner for easy installation Excellent removability even after long-term application Designed to be used with protective over laminate | |

APPLICATIONS

Typical applications include shop windows, architectural building wraps, vehicle window wraps, and other long-term industrial applications.

GENERAL PROPERTIES

| | |
|--------------------------------|--|
| Image quality: | Maximum contrast and great image visibility |
| Printable areas: | 80%, 70%, 60%, 50% (open areas = 20%, 30%, 40%, 50%) hole diameter is 1.5mm and available in 4 patterns |
| Printing inks: | Latex, UV, eco-solvent |
| Adhesion: | Removable, semi-permanent clear adhesive |
| Application temp range: | 50°F - 86°F (+10°C - +30°C) |
| Service temp range: | 0°F - 122°F (-17°C - +50°C) |
| Humidity & solvent resistance: | Good |
| Durability: | 3 years vertical exposure at normal conditions. Tack may increase over time |

FIRE RESISTANCE

M, B1 and ASTM E84 certified

PRODUCT USE ADVISORY

During application, clean window with soap & water only and avoid contact with solvents or ammonia based cleaners. Rinse and dry glass after cleaning. ALWAYS clean and dry glass prior to application. Do not apply on fresh/wet paint or ink, polycarbonate, certain PVC products. For critical substrates, please test prior to application.



Long-term One-way Vision Window Graphic Film

PICTURATM
INTERIORS