

VOYAGER

MATERIAL INFORMATION

Description: Printable polyester/vinyl Type II wallcovering with highly reflective surface

available in silver, black, copper and gold

Width: 54'

Weight: 20oz/Linear Yard (13oz/yd2)

Physicals: Meets or exceeds federal specification CCCW-408-D Type II Class A

No harmful off gassing Low VOC emitting

APPLICATIONS

Standard commercial wallcovering pastes/primers and techniques

Type II Properties

Breaking Strengths, Ibs force:

Machine Direction-warp: Exceeds Type II minimum of 50lbs

Cross Machine Direction-fill: Exceeds Type II minimum of 55lbs

Tearing Strengths, Scale:

Machine Direction-warp Exceeds Type II minimums of 25lbs

Cross Machine Direction-fill Exceeds Type II minimums of 25lbs

Cold Crack Resistance @ 20° F No Change

Heat Aging (7days at 158° F) Does not become stiff, brittle, discolored or

show loss of grain

FIRE CLASSIFICATION: CLASS A – ASTM E-84

Flame and Smoke: Class "A" Fire Rated – tested in accordance with ASTM-E84

Tunnel Test

Flame: 15 Smoke: 205

Passes: ASTM-E84, NFPA-101

The National Fire Protection Association Life Safety Code 101, Section 6-5.3, "Interior Wall and Ceiling Finish Classification", has a means of classifying materials with respect to Flame Spread and Smoke Developed when tested in accordance with NFP A 255, "Method of Test of Surface Burning Characteristics of Building Materials", (ASTM E-84)

PRODUCT USE ADVISORY

Voyager meets the digital printing industry standards for materials that enhance image impact and color, depth, dimension and durability. This product is a Type II commercial digital wallcovering with a Class "A" fire rating.



Metallic, Digitally Printable Wallcovering



