

WINDOW TREATMENTS

PERFORATED SEE-THROUGH FILM

MATERIAL INFORMATION

Description:	Printable perforated film provides optical clarity for see-through viewing from the inside out and vivid graphic visibility when viewing from the outside in. Excellent solution for interior and exterior applications when see-through visibility is required. Removable pressure-sensitive acrylic material bonds well to glass surfaces. Applies well to curved surfaces.	
Width:	54"	
Thickness:	Film	7.2 mil (183) +/- 10%
	Adhesive	0.8 - 0.9 mil (20-30) +/-0.1 (3)
	Liner	7.4 mil (188) +/- 10%
Physicals:	60/40 pattern yields 40% light transmission Clean removability from glass for up to one year Can be overlaminated for protection of graphics against abrasion and cleaning Superior conformability to curved surfaces	

APPLICATIONS

Pressure sensitive product that is easy to install, will stay adhered over a wide range of temperatures and allow for vivid color graphics. Excellent product for all interior and exterior applications that require see-through visibility, including entry door windows, retail and office windows, vehicle windows. Can be easily mounted front or rear surface providing for greater flexibility during installation and conditions.

GENERAL PROPERTIES

Tack (gm/sq cm):	100	ASTM D 2979
Expected exterior life:	Two years	
Dimensional stability:	MD 0.40	Applied shrinkage: 24 hr dwell time on aluminum panel then 24 hrs at 160°F
	TD 0.40	
Ultimate peel:	Average 13 oz/in	ASTM D 903 (modified for 72 hr dwell time)
Service temperature:	-40°F - 176°F	(40°C to 80°C)
Min. application temp:	40°F	(4.5°C)

PRODUCT USE ADVISORY

Not recommended for substrates that are protected with anti-reflection or scratch-resistant coatings, as damage may occur. Not recommended for angled window surfaces.



UV Printable Perforated Window Graphic Film

PICTURA[™]
INTERIORS