# PRIMO

## MATERIAL INFORMATION

PiWc Vinyl

Description:	Multi-color glitter textured surface printable Type II vinyl wallcovering
Width:	54"
Weight:	20oz/Linear Yard (13oz/sq yd)
Physicals:	Meets or exceeds federal specification CCCW-408-D, C, B, A Type II (flame spread, smoke developed and flashover) No harmful off gassing Prop 65 complilant: Cadmium and lead-free formulation

### **APPLICATIONS**

Standard commercial wallcovering pastes/primers and techniques

# Type II Properties

Breaking Strengths, Ibs force:

Machine Direction-warp: Exceeds Type II minimum of 50lbs

Cross Machine Direction-fill: Exceeds Type II minimum of 55lbs

#### Tearing Strengths, Scale:

Machine Direction-warp	Exceeds Type II minimums of 25lbs
Cross Machine Direction-fill	Exceeds Type II minimums of 25lbs
Cold Crack Resistance @ 20° F	No Change

Heat Aging (7days at 158° F)

### FIRE CLASSIFICATION:

### CLASS A – ASTM E-84

Flame and Smoke: ASTM-E84 Tunnel Test Flame: Smoke: Class "A" Fire Rated – tested in accordance with 10 105Passes: ASTM-E84, NFPA-101

Does not become stiff, brittle, discolored or

The National Fire Protection Association Life Safety Code 101, Section 6-5.3, "Interior Wall and Ceiling Finish Classification", has a means of classifying materials with respect to Flame Spread and Smoke Developed when tested in accordance with NFP A 255, "Method of Test of Surface Burning Characteristics of Building Materials", (ASTM E-84)

show loss of grain

### **PRODUCT USE ADVISORY**

This Type II wallcovering grade material is a 2 ply product with a multi color glitter with a scrim type textured surface. Recommended for indoor use or short term outdoor, this product is ideal for murals, special effect signs and wallcovering. This product carries Type II certification for scurbbability, tensile and tear (medium to heavy duty). This product is Class A fire rated and meets NFPA ratings for smoke development.





Multi-Tone Metallic "Glitter" Digitally Printable Wallcovering

